



Safety Data Sheet

Better Chemistry. Better Business

AQUAEASE® SLA 3000

Revised: 7/20/21

1 IDENTIFICATION

Product Name: AQUAEASE® SLA 3000

Product Code :2052003

Recommended use of the chemical and restrictions on use:Industrial applications

Hubbard-Hall Inc.

563 South Leonard Street

Waterbury, CT 06708

Telephone: 203-756-5521

Fax number: 203-756-9017

Emergency Phone Number

CHEMTREC: 1 (800) 424-9300

International: 1 (703) 527-3887

2 HAZARDS IDENTIFICATION



Signal Word: DANGER

Hazard Category: Skin Corrosion/Irritation Hazard Category 1B

Eye Damage/Irritation Hazard Category 1

Corrosive to Metals Hazard Category 1

Hazard Statements: Causes severe skin burns and eye damage.

May be corrosive to metals.

Prevention: Do not breath dusts or mists.

Wash skin thoroughly after handling.

Wear rubber gloves, goggles and chemical protective clothing.

Keep only in original container.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing Rinse skin with water/shower .

Wash contaminated clothing before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call poison center/doctor if you feel unwell.

Specific treatment - refer to poison center or doctor for advice.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Absorb spillage to prevent material damage.

Storage: Store locked up.

Store in corrosive resistant high density polyethylene container.

Disposal: Dispose of contents/container in accordance with local, regional, national, or international regulations.

3 COMPOSITION INFORMATION

Chemical Name	Common Name And Synonyms	CAS No. and other Unique identifiers	Concentration %
Methanesulfonic Acid	-	75-75-2	~20% wt
Diethylene Glycol Butyl Ether	-	112-34-5	~10% wt

4 FIRST AID

After Inhalation:

Remove exposed person to fresh air and support breathing as needed.

After Skin Contact:

Immediately remove contaminated clothing under a safety shower. Flush all affected areas with large amounts of water for 15 minutes. DO NOT attempt to neutralize with chemical agents. Obtain medical advice.

After Eye Contact:

Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Call a physician or poison control center immediately.

After Ingestion:

Call a physician or poison control center immediately. Do not induce vomiting. Immediately rinse mouth and drink plenty of water. If vomiting occurs, keep head low so that the stomach content doesn't get into the lungs. Never give anything by mouth to an unconscious person. Do not use mouth-to-mouth method if victim ingested the substance.

Most Important Symptoms/Effects

Inhalation:

Symptoms may include irritation to the nose, throat and upper respiratory tract.

Eye:

Adverse symptoms may include the following: Symptoms may include redness, pain, blurred vision, eye burns and permanent eye damage.

Skin:

Adverse symptoms may include the following: May cause redness, pain and severe skin burns.

Ingestion:

Adverse symptoms may include the following: Symptoms may include severe burns of the mouth, throat and stomach. Ingestion of large quantities may cause gastrointestinal irritation, vomiting and diarrhea.

5 FIRE FIGHTING MEASURES

Suitable and Unsuitable extinguishing media:

Will not burn or support combustion. Use extinguishing media appropriate for surrounding fire, such as water spray, dry chemical, foam or carbon dioxide.

Special protective equipment and precautions for firefighter

Fire fighters should enter area only if they are protected from all contact with the material. Full protective clothing, including self-contained breathing apparatus, coat, pants, gloves, boots and bands around legs, arms, and waist, should be worn. No skin surfaces should be exposed.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, & Emergency Proc

Wear chemical goggle, gloves and face shield and protective clothing.

Prevent spilled product from drains, sewers, waterways and soil.

Methods and Materials for containment & cleaning up: Absorb the chemical onto sand, vermiculite, or any other non-combustible absorbent, and collect into containers for later disposal.

7 HANDLING AND STORAGE

Precautions for safe handling: Avoid breathing dust, fumes, gas, mist, vapors and sprays.
 Wash hands thoroughly after handling.
 Do not get in eyes, or on skin, or on clothing.

Conditions for safe storage, inc any incompatibilities: Keep container tightly closed.
 Do not allow material to freeze.
 Store in corrosive resistant container.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	Std.	TWA-8hrs	STEL - 15 min.
Methanesulfonic Acid	Not established		-
Diethylene Glycol Butyl Ether	ACGIH	10 ppm (Inhalable fraction and vapor)	-

ACGIH - American Control of Governmental Hygenists
 OSHA - Occupational Safety and Health Administration

Ventilation: Use local exhaust to keep personal exposures below the OSHA Permissible Exposure Limit (s) (PEL) or the ACGIH threshold Limit Values (TLV)Time Weight Average (TWA).

Respiratory Protection: Not required if proper ventilation controls are employed.

Protective Gloves: Acid resistant rubber.

Eye Protection: Wear chemical safety goggles.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear tan colored liquid

Odor: pleasant odor

Odor Threshold: N/A

PH: 1-2 (10% solution)

Melting Point/Freezing Point: N/A

Initial Boiling Point and Boiling Range: N/A

Flash Point: N/A

Evaporation Rate: N/A

Flammability (solid, gas): N/A

Upper/Lower flammability or explosive limits: N/A

Vapor Pressure: N/A

Vapor Density: N/A

Relative Density: 1.0293

Solubility (ies): Complete in water

Partition Coefficient; n-octanol/water: N/A

Auto-ignition Temperature: N/A

Decomposition Temperature: N/A
Viscosity: N/A

10 STABILITY AND REACTIVITY

Reactivity: No specific test data related to reactivity available to this product or its ingredients.
Chemical Stability: Stable under normal conditions
 Corrosive in presence of steel
Possibility of Hazardous Reactions: Reacts violently with strong bases. Contact with metals may release flammable hydrogen gas.
Conditions to Avoid: Extreme humidity, excess heat.
Incompatible Materials: Metals, strong oxidizing agents and strong bases. Do not mix with solutions containing bleach or ammonia.
Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide

11 TOXICOLOGICAL INFORMATION

Oral Administration: Methanesulfonic acid-LD50(Rat)-649 mg/kg
Oral Administration: Diethylene Glycol Butyl Ether-LD50(rat)-3305 mg/kg
Dermal administration: Methanesulfonic acid LD50(Rabbit)->1000 mg/kg
Dermal administration: Diethylene Glycol Butyl Ether, LD50 (rabbit)-2764 mg/kg
Immediate effects: Irritation or burns to skin, eyes and respiratory system
Cancer Hazard: Not listed by IARC, NTP, OSHA, ACGIH
Routes of Exposure Eyes, Skin, Inhalation, Ingestion

12 ECOLOGICAL INFORMATION

Crustations, Daphnia magna, no data available
Persistence and Degradability: Not Available
Bioaccumulation potential: Not known
Soil/Sediment Result: Pronounced solubility and mobility
Other adverse effects(such as hazardous to the ozone layer): Not known

13 DISPOSAL CONSIDERATION

Dispose of in accordance with local, state and federal regulations.

14 TRANSPORT INFORMATION

UN Number: 3265
UN Proper Shipping Name: CORROSIVE LIQUID,ACIDIC,ORGANIC, NOS(ALKANE SULFONIC ACID)
Transport Hazard Class (es): 8
Packing Group: II
ERG: 153

15 REGULATORY INFORMATION

HMIS: Health: 2 Flammability: 0 Reactivity: 0

Sara Hazard Classification Diethylene Glycol Butyl Ether-SARA 313 listed (Glycol Ether)
Proposition 65 No Proposition 65 listed components in this formula

**TSCA Inventory
Status**

All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements .

16 OTHER INFORMATION

Disclaimer: The information is based on our knowledge to date but does not constitute an assurance of product properties and does not imply a legal contractual relationship.