



Safety Data Sheet

Better Chemistry. Better Business

AQUAPURE™ QUICK DROP 20

Revised: 4/21/21

1 IDENTIFICATION

Product Name: AQUAPURE™ QUICK DROP 20

Product Code :2601084

Recommended use of the chemical and restrictions on use:Industrial Wastewater Treatment

Hubbard-Hall Inc.

563 South Leonard Street
Waterbury, CT 06708

Telephone: 203-756-5521

Fax number: 203-756-9017

Emergency Phone Number

CHEMTREC: 1 (800) 424-9300

International: 1 (703) 527-3887

2 HAZARDS IDENTIFICATION



Signal Word: DANGER

Hazard Category: Skin Corrosion/Irritation Hazard Category 2

Eye Damage/Irritation Hazard Category 2B

Carcinogenicity Hazard Category 1A

Specific Target Organ Toxicity (Repeated Exposure) Hazard Category 1

Hazard Statements: Causes skin irritation.

Causes eye irritation.

May cause cancer.

Causes damage to lung.

Prevention: Wash skin thoroughly after handling.

Wear rubber gloves, goggles and chemical protective clothing.

Obtain special instruction before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

Do not breathe dust, fumes, gas, mist, vapors or spray.

Response: If on skin: Wash with plenty of water.

Specific treatment - refer to poison center or doctor for advice.

If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention .
 If exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.

Components with Unknown Oral = 100% Dermal = 100%
Acute Toxicity

3 COMPOSITION INFORMATION

| Chemical Name | Common Name And Synonyms | CAS No. and other Unique identifiers | Concentration % |
|---------------|--------------------------|--------------------------------------|-----------------|
| Silica Quartz | Silica Flour | 14808-60-7 | >1% |

4 FIRST AID

After Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

After Skin Contact:

If on skin(on hair): Take off immediately all contaminated clothing. Rinse with water/safety shower. Call doctor if irritation persists.

After Eye Contact:

If in eyes: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If irritated, call doctor.

Most Important Symptoms/Effects

Inhalation:

Affects respiration and irritates respiratory tract. Acute pneumoconiosis from overwhelming exposure to silica dust has occurred. Coughing and irritation of throat are early symptoms. Inhalation of quartz is classified as a human carcinogen. Risk of cancer depends on duration. May also affect liver.

Eye:

Irritation of eyes and skin.

Skin:

This product can cause mild, transient skin irritation. The severity of irritation will depend on the amount of material that is applied to the skin and the speed and thoroughness that it is removed. Symptoms include redness, itching, and burning of the skin. Repeated or prolonged skin contact can produce moderate irritation(dermatitis).

Chronic:

Chronic exposure can also cause silicosis, a form of lung scarring that can cause shortness of breath, reduced lung function. May also affect blood.

Indication of immediate medical attention:

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Keep victim under observation.

Note to Physicians:

Inhalation may increase the progression of tuberculosis; susceptibility is apparently not increased. Persons with impaired respiratory function may be more susceptible to the effects of the substance . Smoking greatly increases the risk of lung injury. Material is irritating to the mucous membranes and upper respiratory tract.

5 FIRE FIGHTING MEASURES

Suitable and Unsuitable extinguishing media:

Will not burn or support combustion. Use extinguishing media appropriate for surrounding fire, such as water spray, dry chemical, foam or carbon dioxide.

Specific hazards arising from the chemical:

Carbon oxides may be produced.

Special protective equipment and precautions for firefighter

Wear chemical resistant protective equipment and self contained breathing apparatus (SCBA).

6 ACCIDENTAL RELEASE MEASURES

Methods and Materials for containment & cleaning up: Stop spill at source.
 Caution: Spilled material may be slippery.

7 HANDLING AND STORAGE

Precautions for safe handling: Wash hands thoroughly after handling.
 Wear rubber gloves, goggles and chemical protective clothing.
 Eating, drinking and smoking in the work area is prohibited.
 Use NIOSH/MSHA respirators approved for silica bearing dust when free silica containing airborne bentonite dust levels exceed PEL/TLV's. Clean up spills promptly to avoid making dust. Avoid breathing dust. Avoid creating dusty conditions. Quartz silica can become airborne without visible dust cloud.

Conditions for safe storage, inc any incompatibilities: Keep container tightly closed.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

| Name | Std. | TWA-8hrs | STEL - 15 min. |
|---------------|-------|---|----------------|
| Silica Quartz | ACGIH | 0.025 mg/m ³ (Respirable dust) | - |

ACGIH - American Control of Governmental Hygenists
 OSHA - Occupational Safety and Health Administration

Protective Gloves: Rubber gloves
Eye Protection: Wear chemical safety goggles.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Gray powder
Odor: No odor
Odor Threshold: N/A
PH: 4.5-6.5 (5% aqueous suspension)
Melting Point/Freezing Point: N/A
Initial Boiling Point and Boiling Range: N/A
Flash Point: None
Evaporation Rate: N/A
Flammability (solid, gas): Non flammable
Upper/Lower flammability or explosive limits: N/A
Vapor Pressure: N/A
Vapor Density: N/A
Relative Density: 1.0-1.2
Solubility (ies): slightly soluble, forms flocculated suspension
Partition Coefficient; n-octanol/water: N/A
Auto-ignition Temperature: N/A

Decomposition Temperature: N/A

Viscosity: N/A

10 STABILITY AND REACTIVITY

Reactivity: Hazardous Polymerization will not occur.
Chemical Stability: Stable under normal conditions
Possibility of Hazardous Reactions: Hazardous polymerization does not occur.
Incompatible Materials: Avoid contact with strong oxidizers and strong acids.

11 TOXICOLOGICAL INFORMATION

Oral Administration: Not established for this product
Dermal administration: Not established for this product
Immediate effects: Irritation/ burns of skin and eyes.
Immediate effects: Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dusts may not cause noticeable injury or illness even though lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (silicosis).
Cancer Hazard: Silica Quartz-IARC Group I -carcinogenic to humans,ACGIH Class 2A-suspected human carcinogen

12 ECOLOGICAL INFORMATION

Persistence and Degradability: Not Available
Biotic degradability: No data available
Bioaccumulation potential: Unlikely
Water result: Disperses in water.
Soil/Sediment Result: No data available

13 DISPOSAL CONSIDERATION

Dispose of in accordance with local, state and federal regulations.

14 TRANSPORT INFORMATION

UN Proper Shipping Name: NOT D.O.T. REGULATED

15 REGULATORY INFORMATION

HMIS: Health: 2 Flammability: 0 Reactivity: 0

Sara Hazard Classification The chemicals in this product are not subject to SARA Title III , Section 313 Reporting Requirements.
Proposition 65 WARNING! This product contains a chemical or chemicals known to the state of California to cause cancer-Silica,crystalline
TSCA Inventory Status All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements .

16 OTHER INFORMATION

Disclaimer: The information is based on our knowledge to date but does not constitute an assurance of product properties and does not imply a legal contractual relationship.