

Safety Data Sheet

Better Chemistry. Better Business

MAE STRAUMANN BLEND

Revised: 11/3/2020

1 IDENTIFICATION

Product Name: MAE STRAUMANN BLEND

Product Code:0001064

Recommended use of the chemical and restrictions on use:Industrial applications

Hubbard-Hall Inc.

563 South Leonard Street Waterbury, CT 06708 **Telephone**: 203-756-5521 **Fax number:** 203-756-9017

Emergency Phone Number **CHEMTREC:** 1 (800) 424-9300 **International:** 1 (703) 527-3887

2 HAZARDS IDENTIFICATION









Signal Word: DANGER

Hazard Category: Acute Toxicity-Inhalation Hazard Category 4

Skin Corrosion/Irritation Hazard Category 1A Eye Damage/Irritation Hazard Category 1 Acute Aquatic Toxicity-Category 3

Chronic Aquatic Toxicity- Category 3 Carcinogenicity Hazard Category 1A

Specific Target Organ Toxicity (Repeated Exposure) Hazard Category 2

Corrosive to Metals Hazard Category 1

Hazard Statements: Harmful if inhaled.

May cause damage to teeth through prolonged or repeated exposure via inhalation.

Causes severe skin burns and eye damage.

May cause cancer.

Harmful to aquatic life with long lasting effects

May be corrosive to metals.

Prevention: Avoid breathing dust, fumes, gas, mist, vapors and sprays.

Use only outdoors or in well ventilated area.

Wash skin thoroughly after handling.

Wear protective gloves, chemical protective clothing, eye protective goggles and face

shield for face protection.

Obtain special instruction before use.

Do not handle until all safety precautions have been read and understood.

Keep only in original container.

Avoid releases to the environment

Response: If inhaled: Remove person to fresh air and keep comfortable for breathing.

Immediately call poison center or doctor and explain the type of exposure to the

chemical(s) and provide the name of the chemical(s).

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing Rinse skin with water/shower .

Wash contaminated clothing before reuse.

Specific treatment - refer to poison center or doctor for advice.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Absorb spillage to prevent material damage .

Storage: Store locked up.

Store in well ventilated place. Keep container tightly closed.

Store in corrosive resistant high density polyethylene container.

Disposal: Dispose of contents/container in accordance with local, regional, national, or

international regulations.

COMPOSITION INFORMATION

Chemical Name	Common Name And Synonyms	CAS No. and other Unique identifiers	Concentration %
Sulfuric Acid	Oil of Vitriol	7664-93-9	<35%
Hydrochloric Acid	-	7647-01-0	<15%

FIRST AID

After Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

After Skin Contact:

Immediately remove contaminated clothing under a safety shower. Flush all affected areas with large amounts of water for 15 minutes. DO NOT attempt to neutralize with chemical agents. Obtain medical advice.

After Eve Contact:

Immediately flush the eyes with large quantities of running water for 15 minutes. Hold the eyelids apart during the flushing to ensure rinsing of the entire surface of the eyelids with water. DO NOT attempt to neutralize with chemical agents. Obtain medical attention as soon as possible. Oils or ointments should not be used. Continue rinsing for an additional 15 minutes if the physician is not available.

After Ingestion:

If swallowed: Rinse mouth. Do NOT induce vomiting.

5 FIRE FIGHTING MEASURES

Suitable and Unsuitable extinguishing media:

Avoid contact with water. Use foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical:

Sulfur dioxide may be produced.

Special protective equipment and precautions for firefighter

Fire fighters should enter area only if they are protected from all contact with the materail. Full protective clothing, including self-contained breathing apparatus, coat, pants, gloves, boots and bands around legs, arms, and waist, should be worn. No skin surfaces should be exposed.

ACCIDENTAL RELEASE MEASURES

Methods and Materials for containment & cleaning up:

If trained in accordance 29 CFR 1910.120, leaks should be stopped. Spills should be contained and cleaned immediately. Persons performing clean up work should wear adequate personal protective equipment and clothing. Spills and releases should be reported, if required, to the appropriate local, state and federal regulatory agencies.

Neutralize spill with soda ash or lime under good ventilation. For an interior (inside a closed space) spill be aware that the use of Soda Ash, Lime will eveolve heat and carbon dioxide thus the need for ventilation.

Avoid release to the environment.

HANDLING AND STORAGE

Precautions for safe handling: Use ventilation sufficient to keep personal exposure below the OSHA Permissible

Exposure Limits (PEL) and or the ACGIH Threshold Limit Value (TLV) Time Weighted

Average (TWA) exposure limits.

Wear rubber protective gloves, chemical protective clothing, eye protective goggles and

face shield for face protection.

Avoid breathing dust, fumes, gas, mist, vapors and sprays.

Eating, drinking and smoking in the work area is prohibited.

Do not get in eyes, or on skin, or on clothing.

Keep only in original container.

Keep container tightly closed.

Conditions for safe storage, inc any incompatibilities:

Store in corrosive resistant container.

Store locked up and away from incompatible chemicals.

Store in cool dry place.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Name	Std.	TWA-8hrs	STEL - 15 min.
Sulfuric Acid	ACGIH	0.2 mg/m3	-
Hydrochloric Acid	ACGIH	2 ppm	-

ACGIH - American Control of Governmental Hygenists OSHA - Occupational Safety and Health Administration

Ventilation: Use local exhaust to keep personal exposures below the OSHA Permissible Exposure Limit(s)

(PEL) or the ACGIH threshold Limit Values (TLV)Time Weight Average (TWA).

Respiratory Protection: A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI 788.2 or

applicable federal requirements must be followed whenever work place conditions warrant respirator use. NIOSH's Respirator Decision Logic" may be useful in determining the suitability

of various types of respirators.

Protective Gloves: Acid resistant rubber.

Eye Protection: Wear chemical safety goggles with face shield.

Other Protective Rubber aprons, safety shoes and similar protective clothing.

Equipment:

PHYSICAL AND CHEMICAL PROPERTIES

Clear to turbid oily liquid Appearance: Odor: Acrid, pungent, Irritating odor.

Odor Threshold:

PH: (1% solution in water)<1

Melting Point/Freezing Point: -74 °C N/A

Initial Boiling Point and Boiling

Range:

Flash Point: N/A **Evaporation Rate:** N/A N/A Flammability (solid, gas): Upper/Lower flammability or N/A

explosive limits: Vapor Pressure:

190 mm Hg @ 25 °C

N/A Vapor Density: 1.3-1.5 **Relative Density:**

Complete in water Solubility (ies):

Partition Coefficient; N/A

n-octanol/water:

Auto-ignition Temperature:

Decomposition Temperature:

N/A N/A

N/A Viscosity:

10 STABILITY AND REACTIVITY

Reacts violently with water, organic substances and base solutions with evolution of heat and Reactivity:

hazardous mists.

Chemical Stability: Stable under normal conditions Extremely high temperatures Conditions to Avoid:

Vigorous reactions with: water; alkaline solutions; metals, metal powder, **Incompatible Materials:**

> Cabides; Chlorates; Fulminates; nitrates, picrates, strong oxidizing, reducing, or combustible organic materials. Hazardous gases are evolved in contact with chemicals such as cyanides, sulfides, and carbides. Sulfuric acid reacts with metal to produce hydrogen, a flammable and potentialy explosive gas. Hydrogen reacts with sulfides and generates hydrogen sulfide(Highly toxic gas). NEVER add water directly to sulfuric acid because a violent exothermic reaction

may occur.

Hazardous Decomposition

Products:

Possibility of decomposition if heated and in contact with sources of ignition. Releases of toxic

gases and vapors (Sulfur oxides (SO2,SO3)).

Extreme heat may cause the product to decompose, producing toxic fumes which may include

chlorine compounds.

11 TOXICOLOGICAL INFORMATION

Oral Administration: Sulfuric Acid-LD50-(Rat)-2140 mg/kg

Hydrochloric Acid-LD50:700 mg/kg (31.5%) rat **Oral Administration:**

Inhalation: Sulfuric Acid-LC50-(Rat)-347 ppm-1 h

Corrosive! Inhalation on vapors can cause coughing, choking, inflammation of the nose, throat, Inhalation:

and upper respiratory tract, and in severe cases, pulmonary edema, circulatory failure, and

death.

Dermal administration: Hydrochloric Acid-LD50:>5010 mg/kg (31%) Rabbit Immediate effects: Severe irritation or burns to skin, eyes and respiratory system

Long term exposure: Long term exposure to concentrated vapors may cause erosion of the teeth. Long term

exposure seldom due to corrosive properties of the acid.

Cancer Hazard: IARC group 1-Carcinogenic to Humans(Strong inorganic mists containing Sulfuric

acid),ACGIH-A2-Suspected Human Carcinogen.

Routes of Exposure Eyes, Skin, Inhalation, Ingestion

12 ECOLOGICAL INFORMATION

Fish, Lepomis macrochirus, Sulfuric Acid,LC50-48 h-49 mg/L

Daphnia Magna, Sulfuric Acid-EC50,48 h-60-70 mg/L

Persistence and Not Available

Degradability:

Bioaccumulation potential: Unlikely

Water result: Disperses in water.

Soil/Sediment Result: No data available

13 DISPOSAL CONSIDERATION

Dispose of in accordance with local, state and federal regulations.

14 TRANSPORT INFORMATION

UN Number: 3264

UN Proper Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (SULFURIC ACID AND

HYDROCHLORIC ACID),

15 REGULATORY INFORMATION

HMIS: Health: 3 Flammability: 0 Reactivity: 1

Cercla Sulfuric Acid-RQ=1000 lbs
Cercla Hydrochloric Acid-RQ-5000 lbs
Sara Hazard Hydrochloric Acid-SARA 313 listed

Classification

Sara Hazard Sulfuric Acid-Subject to reporting levels established by SARA Title III, Section 313

Classification

Proposition 65 WARNING! This product contains a chemical known in the State of California to cause cancer.

Strong inorganic mists containing sulfuric acid.

TSCA Inventory All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements.

Status

16 OTHER INFORMATION

REACH status No **RoHS** or **REACH SVHC** are contained in this product.

Disclaimer: The information is based on our knowledge to date but does not constitute an assurance of product

properties and does not imply a legal contractual relationship.

Date Prepared: 9/29/14