



Safety Data Sheet

Better Chemistry. Better Business

MAINTENANCE CLEANER #10

Revised: 9/15/17

1 IDENTIFICATION

Product Name: MAINTENANCE CLEANER #10

Product Code :2052063

Recommended use of the chemical and restrictions on use:Alkaline Cleaner

Hubbard-Hall Inc.

563 South Leonard Street

Waterbury, CT 06708

Telephone: 203-756-5521

Fax number: 203-756-9017

Emergency Phone Number

CHEMTREC: 1 (800) 424-9300

International: 1 (703) 527-3887

2 HAZARDS IDENTIFICATION



Signal Word: DANGER

Hazard Category: Corrosive to Metals Hazard Category 1

Acute Toxicity-Oral Hazard Category 4

Skin Corrosion/Irritation Hazard Category 1A

Eye Damage/Irritation Hazard Category 1

Hazard Statements: May be corrosive to metals.

Harmful if swallowed.

Causes severe skin burns and eye damage.

Prevention: Keep only in original container.

Wear protective gloves, chemical protective clothing, eye protective goggles and face shield for face protection.

Do not eat, drink or smoke when using this product.

Do not breath dusts or mists.

Wash skin thoroughly after handling.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Immediately call poison center or doctor and explain the type of exposure to the chemical(s) and provide the name of the chemical(s).
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 Specific treatment - refer to poison center or doctor for advice.

Storage: Store locked up.

Store in corrosive resistant high density polyethylene container.

Disposal: Dispose of contents/container in accordance with local, regional, national, or international regulations.

3 COMPOSITION INFORMATION

| Chemical Name | Common Name And Synonyms | CAS No. and other Unique identifiers | Concentration % |
|-------------------------------|--------------------------|--------------------------------------|-----------------|
| Sodium Hydroxide | Caustic Soda | 1310-73-2 | Approx 2% |
| Sodium Metasilicate | Disodium Metasilicate | 6834-92-0 | Approx 2% |
| Diethylene Glycol Butyl Ether | - | 112-34-5 | Approx 10% |
| Sodium Tripolyphosphate | - | 7758-29-4 | Approx 5% |

4 FIRST AID

After Inhalation:

Move to fresh air. If breathing is difficult, give oxygen. If breathing stops, provide artificial respiration. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one way valve or other proper respiratory device. Call a physician or poison control center immediately.

After Skin Contact:

Take off immediately all contaminated clothing. Wash off IMMEDIATELY with plenty of water for at least 15-20 minutes. Get medical attention immediately! Wash clothing separately before reuse. Destroy or thoroughly clean all contaminated shoes.

After Eye Contact:

Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Call a physician or poison control center immediately.

After Ingestion:

Call a physician or poison control center immediately. Do not induce vomiting. Immediately rinse mouth and drink plenty of water. If vomiting occurs, keep head low so that the stomach content doesn't get into the lungs. Never give anything by mouth to an unconscious person. Do not use mouth-to-mouth method if victim ingested the substance.

Most Important Symptoms/Effects

Delayed:

Burning pain and severe corrosive skin damage. Permanent eye damage including blindness could result. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Shortness of breath.

Indication of immediate medical attention:

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Keep victim under observation.

Special Precautions / Procedures:

Emergency personnel should protect against secondary contamination.

5 FIRE FIGHTING MEASURES

Suitable and Unsuitable extinguishing media:

Water fog. Foam. Dry Chemical powder. Carbon Dioxide (CO2). Use extinguishing agent suitable for type of surrounding fire. Do not use solid water stream as it may scatter and spread fire. Do not use halogenated extinguishing agents.

Specific hazards arising from the chemical:

The product itself does not burn. May decompose upon heating to produce corrosive and/or toxic fumes. Contact with metal may release flammable hydrogen gas.

Special protective equipment and precautions for firefighter

Fire fighters should enter area only if they are protected from all contact with the material. Full protective clothing, including self-contained breathing apparatus, coat, pants, gloves, boots and bands around legs, arms, and waist, should be worn. No skin surfaces should be exposed.

6 ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment, & Emergency Proc**

Prevent spilled product from drains, sewers, waterways and soil.

Wear appropriate chemical protection equipment such as gloves, face-shield, goggles and suitable body protection to prevent contamination of skin, eyes and personal clothing.

Methods and Materials for containment & cleaning up:

If trained in accordance 29 CFR 1910.120, leaks should be stopped. Spills should be contained and cleaned immediately. Persons performing clean up work should wear adequate personal protective equipment and clothing. Spills and releases should be reported, if required, to the appropriate local, state and federal regulatory agencies.

7 HANDLING AND STORAGE**Precautions for safe handling:**

Use caution when combining with water. DO NOT add water to Caustic. ALWAYS add caustic to water while stirring to minimize heat generation. Do not get in eyes, skin or on clothing. Do not taste or swallow. Do not breath vapor or mist. Use only with adequate ventilation. Wear appropriate personal protective equipment. Transfer and storage systems should be compatible and corrosion resistant. Observe good industrial hygiene practices.

Conditions for safe storage, inc any incompatibilities:

Keep container tightly closed.

Store in cool dry place.

Store away from incompatible materials. (See section 10).

Do not allow material to freeze.

Store in corrosive resistant container.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

| Name | Std. | TWA-8hrs | STEL - 15 min. |
|-------------------------------|-----------------|---------------------------------------|----------------|
| Sodium Hydroxide | ACGIH | 2 mg/m ³ | |
| Diethylene Glycol Butyl Ether | ACGIH | 10 ppm (Inhalable fraction and vapor) | |
| Sodium Tripolyphosphate | ACGIH | 10 mg/m ³ as nuisance dust | |
| Sodium metasilicate | Not established | | |

ACGIH - American Control of Governmental Hygenists
OSHA - Occupational Safety and Health Administration

Ventilation:

Use local exhaust to keep personal exposures below the OSHA Permissible Exposure Limit (s) (PEL) or the ACGIH threshold Limit Values (TLV)Time Weight Average (TWA).

Protective Gloves:

Rubber gloves

Eye Protection:

Wear chemical safety goggles with face shield.

Other Protective Equipment:

Wear chemical resistant apron.

9 PHYSICAL AND CHEMICAL PROPERTIES**Appearance:**

Yellow Liquid

| | |
|--|-------------------|
| Odor: | Soap like odor |
| Odor Threshold: | N/A |
| PH: | 13.3 |
| Melting Point/Freezing Point: | N/A |
| Initial Boiling Point and Boiling Range: | N/A |
| Flash Point: | N/A |
| Evaporation Rate: | N/A |
| Flammability (solid, gas): | N/A |
| Upper/Lower flammability or explosive limits: | N/A |
| Vapor Pressure: | N/A |
| Vapor Density: | N/A |
| Relative Density: | 1.05 |
| Solubility (ies): | Complete in water |
| Partition Coefficient; n-octanol/water: | N/A |
| Auto-ignition Temperature: | N/A |
| Decomposition Temperature: | N/A |
| Viscosity: | N/A |

10 STABILITY AND REACTIVITY

| | |
|--|---|
| Reactivity: | Contact with metal may release flammable hydrogen gas. |
| Chemical Stability: | Stable under normal conditions |
| Possibility of Hazardous Reactions: | Hazardous polymerization does not occur. |
| Conditions to Avoid: | Reacts violently with strong acids. This product may react with oxidizing agents. Do not mix with other chemicals. Corrosive to aluminum, tin, zinc, copper and most alloys in which they are present including brass and bronze. Corrosive to steels at elevated temperatures above 40 °C. |
| Incompatible Materials: | Avoid contact with aluminum, tin, zinc, halogenated solvents, and strong oxidizers and acids. |
| Hazardous Decomposition Products: | Contact with metal (aluminum, zinc, tin) and sodium tetrahydroborate liberates hydrogen gas. |

11 TOXICOLOGICAL INFORMATION

| | |
|-------------------------------|---|
| Oral Administration: | Caustic 50% solution: LD50, Rat-300-500 mg/kg |
| Oral Administration: | Sodium Metasilicate-(Rat-male and female) LD50-1152-1349 mg/kg |
| Oral Administration: | Diethylene Glycol Butyl Ether-LD50(rat)-3305 mg/kg |
| Dermal administration: | Caustic 50% solution-LD50 Rabbit->2 g/kg |
| Dermal administration: | Diethylene Glycol Butyl Ether, LD50 (rabbit)-2764 mg/kg |
| Immediate effects: | Severe irritation or burns to skin, eyes and respiratory system |
| Cancer Hazard: | Not listed by IARC, NTP, OSHA, ACGIH |

12 ECOLOGICAL INFORMATION

| | |
|--|------------------------------------|
| Fish, <i>Lepomis macrochirus</i>, | Caustic-99 mg/L, 48 hrs |
| Bioaccumulation potential: | Unlikely |
| Water result: | Disperses in water. |
| Soil/Sediment Result: | Pronounced solubility and mobility |

13 DISPOSAL CONSIDERATION

Dispose of in accordance with local, state and federal regulations.

14 TRANSPORT INFORMATION

UN Number: 1760
UN Proper Shipping Name: CORROSIVE LIQUID, N.O.S.(SODIUM HYDROXIDE, SODIUM METASILICATE),
Transport Hazard Class (es): 8
Packing Group: III
ERG: 154

15 REGULATORY INFORMATION

HMIS: Health: 3 Flammability: 0 Reactivity: 0

Cercla Sodium Hydroxide-RQ=1000 lbs

Sara Hazard Classification SARA 302 - Extremely Hazardous Substances; None present

Sara Hazard Classification SARA Hazard Categories: Immediate Hazard:Yes Delayed Hazard:Yes Fire Hazard-No Pressure Hazard-No Reactivity Hazard-yes

Sara Hazard Classification Diethylene Glycol Butyl Ether-SARA 313 listed (Glycol Ether)

16 OTHER INFORMATION

No **RoHS** or **REACH SVHC** are contained in this product.

Disclaimer: The information is based on our knowledge to date but does not constitute an assurance of product properties and does not imply a legal contractual relationship.

Date Prepared: 8/17/14